

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

**Product Name:** Coastcote Etch Primer- Red Oxide (SNK 2)

**Company Name:** Kansai Plascon (Pty) Ltd  
**Address:** P.O. Box 4010  
 Luipaardsvlei  
 1743

**Telephone:** (011) 951 4500  
**Facsimile:** (011) 955 2841  
**Contact Person:** Mr.C.Costa

## SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical Class:** Phenolic resin based coating  
**Classification:** F, Xn  
**R Phrases:** R11, 20, 41, 65  
**S Phrases:** S2, 13, 51, 62

HAZARDOUS COMPONENTS	% (w/w)	CAS No.	E.C. No.
PROPANOL	> 10	71-23-8	603-003-00-0
N BUTANOL	< 10	71-36-3	603-004-00-6
TOLUENE	10	108-88-3	601-021-00-3

Volatile organic compounds (VOC): 717 g/l

## SECTION 3. HAZARDS IDENTIFICATION

**SAPMA Health Rating:** 2-MODERATE - Temporary or minor injury possible even if treatment given

**Inhalation:** HARMFUL. Excessive exposure to this material must be avoided.

**Skin:** Causes irritation. May be absorbed through intact skin.

**Eyes:** Irritating.

**Ingestion:** Harmful, may cause lung damage if swallowed.

No carcinogenic, mutagenic or genetic effects established  
 May have short term environmental effects. Contain, monitor & remove.



## SECTION 4. FIRST AID MEASURES

**Inhalation :** Move to fresh air. In case of discomfort seek medical attention.

**Skin :** Wash with water and a recognised skin cleaner. In severe cases refer to Doctor.

**Eyes :** Rinse immediately with plenty of water. Seek medical advice if symptoms persist.

**Ingestion :** Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical attention.

## SECTION 5. FIRE FIGHTING MEASURES

Highly flammable with toxic fumes. Can form explosive vapour/air mixture. Static discharge hazard.  
 In fire use foam or dry powder. Use fog to cool and control. Do not use water jets. Cool containers in case of fire.

## SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Ensure sufficient ventilation. Eliminate all ignition sources.  
 Contain & collect spillage with non combustible absorbent material and dispose of according to local regulations  
 Keep out of drains and sewers

## SECTION 7. HANDLING AND STORAGE

Keep in original container  
 Keep away from ignition sources, flames, sparks, static and heat. No Smoking.  
 Store in a well ventilated, cool and dry environment. Store away from direct sunlight, heat and severe cold.  
 Avoid free fall of liquid - use earthing.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	CAS	OEL (mg/m3)	OEL (ppm)	STOEL (ppm)	STOEL (mg/m3)
PROPANOL	71-23-8	500	200	625	250 RL S
TOLUENE	108-88-3	188	50	560	150 RL+S
N BUTANOL	71-36-3	150	50	150	50 RL S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

**SAPMA Rating:** 2-H-E PPE : Respirator and Eye protection  
**Inhalation:** In case of insufficient ventilation, use suitable respiratory protection.  
**Skin:** AVOID CONTACT. Use impervious gloves, apron and boots.  
**Eyes:** Use goggles. Avoid direct contact.  
**Ingestion:** Observe the rules of hygiene. Wash before eating, drinking or smoking.



## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Opaque red liquid  
**Flash Point :** < 23 °C  
**Viscosity :** 50-55 sec (Ford Cup no. 4)  
**Density:** 1.02 kg/ℓ (typical)  
**Solubility:** Soluble in organic solvents, insoluble in water

## SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions. Inert - no reaction with fire-fighting water

## SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established.

## SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove.

## SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors and dispose of according to local by laws. Exercise care with used containers.

## SECTION 14. TRANSPORT INFORMATION

**SIN/UN no:** 1263  
**Packaging group:** II  
**Class:** 3.2  
**Shipping name:** PAINT



## SECTION 15. REGULATORY INFORMATION

**Classification:** F, Xn

R11	Highly flammable
R20	Harmful by inhalation
R41	Risk of serious damage to eyes.
R65	Harmful: may cause lung damage if swallowed.
S2	Keep out of reach of children
S13	Keep away from food, drink and animal feed stuffs.
S51	Use only in well ventilated areas
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show the container or label.

## SECTION 16. OTHER INFORMATION

Take precautionary measures against static discharges. In case of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.